

BESSEY Product Training



BESSEY Tools North America
One Hand Clamps (EZS, DUO & PG)

Woodworking: One Hand Clamps (EZS)



Simply better.

- 1) Powerful technology: The very precise engineering and production tolerances permit clamping force of up to 445 lbs
- 2) Intelligent release button allows the clamp's fixed jaw to be reversed to allow for spreading. No pieces to lose and no tools required.
- 3) Ergonomic handle permits one to apply full force from behind the rail without impeding working area
- 4) Soft pressure caps do not mar the woodworking surface



Woodworking: One Hand Clamps (EVS)



Simply better.

EVS Series:

- q Capacities available: 6", 12", 18", 24" & 36"
- q Profiled rail for greater rail rigidity
- q Throat Depth = 3-1/2"
- q Clamping Force rating up to 445 lbs



Woodworking: One Hand Clamps (DUO)



Simply better.

- 1) Unique technology: A lighter touch but, very large jaw surfaces for a one-hand clamp. The impact and fracture resistant jaws allow for a soft touch on the work surface
- 2) Clamping and spreading with the turn of a dial; nothing to reverse other than the dial and, you are ready to spread or clamp
- 3) Ergonomic handle runs parallel to the rail for a straight-line approach to the work surface
- 4) Soft pressure caps do not mar the woodworking surface



Woodworking: One Hand Clamps (Duo)



Simply better.

DUO Series:

- q 2.5" throat depth, 180 lbs clamp force
- q Capacity of : 6" & 12"
- q 3.5" throat depth, 260 lbs clamp force
- q Capacity of : 6", 12", 18" & 24"



Woodworking: DuoKlamp Extender (DKX)



Simply better.

- 1) The perfect accessory when a very long clamp is needed.
- 2) Works in conjunction with the DuoKlamp...
- 3) The DuoKlamp rail is slid into the pre-formed slot on the DKX to form an extended clamp arrangement
- 4) Clamp capacity using any DuoKlamp and the DKX is 65"
- 5) Spreading capacity using any DuoKlamp and the DKX is 70"



Woodworking: One Hand Clamps (PG)



Simply better.

- 1) Class leading power: A one hand woodworking clamp with 1000 lbs of clamping force. Apply initial pressure with one hand using the pump handle and tighten the clamp using the 2K Handle and spindle (with ACME thread)
- 2) Quick release button right where you need it
- 3) Plastic pressure caps to avoid marring your wood
- 4) 12" and 24" capacities available, 4" throat depth, 1000 lbs clamp force



Thank you for your attention!

BESSEY Tools North America