

# BESSEY® Chemicals & Compounds



Relton Fluids and Compounds

Simply better.

## Relton Fluids & Compounds

### Relton Stick-Kut™ Lubricating Stick Wax

- For grinding wheels, sanding belts and saw blades
- Eliminates heat build up and belt loading - extends wheel life



### Relton Dark and Light Thread Cutting Oil

- Reduces friction; longer tool life; clean burr free thread
- Forms tough film - for use on a wide variety of materials



### Relton Rel Saw™ Semi-Synthetic Band-Saw Fluid

- Improves blade life; reduces machine wear
- Contains rust and corrosion inhibitors



### Relton Option 1 cutting fluid

- Water based; Non-WHMIS-environmentally friendly
- No chlorine, no sulphur, non-toxic formula is safe to use



### Relton A9 Aluminum Cutting Fluid

- Specifically for aluminum - use for tapping, drilling, boring, milling, turning, broaching, reaming and sawing
- May be used on other metals; Non-WHMIS - environmentally friendly



### Relton Air-Flo Air Tool Oil

- High quality air tool and air line lubricant



**Relton fluids and compounds are only available in Canada**

Rev. Jan 24-2012

Catalog Number	Unit/Container Imperial/Metric
----------------	--------------------------------

### Relton Stik-Kut™ Lubricating Stick Wax

15-SK	15 oz stick
-------	-------------

### Relton Dark Thread Cutting Oil

TCO14-01G	1 US gal/3.785 L
TCO14-05G	5 US gal/18.925 L

### Relton Light Thread Cutting Oil

TCO16-01G	1 US gal/3.785 L
TCO16-05G	5 US gal/18.925 L

### Relton Rel Saw™ Semi-Synthetic Band Saw Fluid

01G-RS	1 US gal/3.785 L
05G-RS	5 US gal/18.925 L

### Relton Option 1 Cutting Fluid

OPT114	4 oz/118 ml
OPT455	16 oz/455 ml
OPT4	1 US gal/3.785 L
OPT20	5 US gal/18.925 L
OPT205	45 gal/170.325 L

### Relton A9 Aluminum Cutting Fluid

A9114	4 oz/118 ml
A9455	16 oz/455 ml
A94	1 US gal/3.785 L
A920	5 US gal/18.925 L
A9205	45 gal/170.325 L

### Relton Air-Flo Air Tool Oil

AF-PNT	1 pint/.47 L
AF-01G	1 US gal/3.785 L

