The evolution of the K Body REVO

With greater power and safety in a new design





Precise and gentle

Workpieces with sensitive surfaces can be clamped and spread exactly parallel to each other — even behind and on the side of the rail. Corners and recessed edges as well as pointed and round surfaces can also be perfectly aligned:





Powerful and safe

They securely clamp with a clamping force of up to 8.000 N:

- due to the metal-reinforced plastic housing
- due to the optimised sliding arm with double slide protection: It holds the clamp reliably with the set clamping force and prevents any unintentional slipping of the sliding arm in the unclamped condition

Versatile and well thought out

The clamps provide an enormous number of possible applications:

- due to ingenious accessories, such as tilting adapter, frame press set, clamp extension and table clamp
- the ergonomically formed 2-component symmetrical plastic handle with hexagon socket means the clamping force can be comfortably applied (max. torque 17 Nm)
- the continuously adjustable head for the KREV Vario version enables the clamp to be positioned in the middle of the workpiece for optimum weight distribution




- Clamping force up to 8.000 N
- Very large parallel clamping surfaces with 3 removable pressure caps
- Metal-reinforced plastic housing and optimised sliding arm with double slide protection for more power and safety: The set clamping force is maintained and the sliding arm cannot unintentionally slip in the unclamped condition
- Can be converted without tools for spreading tasks
- High-quality 2-component symmetrical plastic handle with hexagon socket for the comfortable application of the clamping force (max. torque 17 Nm)
- KREV with continuously adjustable and fixable upper section for optimum positioning on the workpiece
- Steplessly adjustable and fixable upper section for improved workpiece positioning
- Very large parallel clamping surfaces
- With 2 pressure caps to protect delicate surfaces
- Can be converted to spreading function with no need for tools
- KP Framing System (from 30 cm to 250 cm/12"-98") with four 90° KP Blocks
- Separately adjustable clamping force with 2 inserted clamps per corner
- Lightweight / easy to assemble
- On carded hang pack
- Adapter with tilting clamping jaws with a tilt range of -15° to +15°
- Clamping on sloping and parallel surfaces
- On carded hang pack
- Connect any two K Body parellel clamps to increase the clamping capacity. The connector is made of robust aluminum.
- On carded hang pack
- Especially for DIY applications and domestic appliances
- Special accessory for angle clamps WS 3/WS 6, screw clamp S 10 and K Body REVO parallel clamps KRE / KREV and KR / KRV to hold them to a work surface edge



K Body REVO KRE and Vario K Body REVO KREV


•	Order- No.	←a →	← b →	← e →	←X →	44	Ø	
ı		mm	mm	mm	mm	kg	qty.	V3
	KRE30-2K	300	95	255-390	29 x 9	2.15	2	
	KRE60-2K	600	95	255-730	29 x 9	2.76	2	
	KRE80-2K	800	95	255-930	29 x 9	3.10	2	
	KRE100-2K	1000	95	255-1130	29 x 9	3.45	2	
	KRE125-2K	1250	95	255-1355	29 x 9	3.87	2	
	KRE150-2K	1500	95	255-1610	29 x 9	4.28	2	
	KRE200-2K	2000	95	255-2080	29 x 9	5.09	2	
	KRE250-2K	2500	95	255-2580	29 x 9	6.05	2	
	KREV100-2K	1000	95	260-1130	29 x 9	3.77	2	
	KREV150-2K	1500	95	260-1610	29 x 9	4.25	2	
	KREV200-2K	2000	95	260-2080	29 x 9	5.30	2	
	KREV250-2K	2500	95	260-2580	29 x 9	6.30	2	












Order- No.	Suitable for	44	Ø	
		kg	qty.	V3
KRE-VO	KRE / KREV / KR / KRV	0.59	12	



Framing set KP

Order- No.	Suitable for	44	Ø	
		kg	qty.	V3
KP	KRE / KREV / KR / KRV	0.55	12	

Contents: 4 rail couplings and 4 adapters















Tilting K Body clamp adapter KR-AS (2 pcs./bag)

Order- No.	Suitable for	44	Ø	
		kg	qty.	V3
KR-AS	KRE / KREV / KR / KRV	0.18	12	

K Body Extender KBX

Order- No.	Suitable for	4	Ø	
		kg	qty.	V3
KBX20	KRE / KREV / KR / KRV	0.75	12	

Table clamp TK6

Order- No.	Suitable for	44	Ø	
		kg	qty.	V3
TK6	KRE / KREV / KR / KRV	0.10	50	

For further information www.bessey.de







Your dealer: